

O-Ring Standard Size (BS 4518)

O-Ring Standard Size (BS 4518)

MEASUREMENTS IN MILLIMETERS				MEASUREMENTS IN INCHES				MEASUREMENTS IN MILLIMETERS				MEASUREMENTS IN INCHES			
ID	±	CS	±	ID	±	CS	±	ID	±	CS	±	ID	±	CS	±
3.10	0.14	1.60	0.08	0.122	0.006	0.063	0.003	37.60	0.39	2.40	0.09	1.480	0.015	0.094	0.004
4.10	0.14	1.60	0.08	0.161	0.006	0.063	0.003	39.60	0.41	2.40	0.09	1.559	0.016	0.094	0.004
5.10	0.15	1.60	0.08	0.201	0.006	0.063	0.003	41.60	0.42	2.40	0.09	1.638	0.017	0.094	0.004
6.10	0.16	1.60	0.08	0.240	0.006	0.063	0.003	44.60	0.44	2.40	0.09	1.756	0.017	0.094	0.004
7.10	0.17	1.60	0.08	0.280	0.007	0.063	0.003	45.60	0.45	2.40	0.09	1.795	0.018	0.094	0.004
8.10	0.18	1.60	0.08	0.319	0.007	0.063	0.003	47.60	0.46	2.40	0.09	1.874	0.018	0.094	0.004
9.10	0.18	1.60	0.08	0.358	0.007	0.063	0.003	49.60	0.48	2.40	0.09	1.953	0.019	0.094	0.004
10.10	0.19	1.60	0.08	0.398	0.007	0.063	0.003	51.60	0.49	2.40	0.09	2.031	0.019	0.094	0.004
11.10	0.20	1.60	0.08	0.437	0.008	0.063	0.003	54.60	0.51	2.40	0.09	2.150	0.020	0.094	0.004
12.10	0.21	1.60	0.08	0.476	0.008	0.063	0.003	55.60	0.52	2.40	0.09	2.189	0.020	0.094	0.004
13.10	0.21	1.60	0.08	0.516	0.008	0.063	0.003	57.60	0.53	2.40	0.09	2.268	0.021	0.094	0.004
14.10	0.22	1.60	0.08	0.555	0.009	0.063	0.003	58.60	0.54	2.40	0.09	2.307	0.021	0.094	0.004
15.10	0.23	1.60	0.08	0.594	0.009	0.063	0.003	59.60	0.55	2.40	0.09	2.346	0.022	0.094	0.004
16.10	0.24	1.60	0.08	0.634	0.009	0.063	0.003	61.60	0.56	2.40	0.09	2.425	0.022	0.094	0.004
17.10	0.24	1.60	0.08	0.673	0.009	0.063	0.003	62.60	0.57	2.40	0.09	2.465	0.022	0.094	0.004
18.10	0.25	1.60	0.08	0.713	0.010	0.063	0.003	64.60	0.58	2.40	0.09	2.543	0.023	0.094	0.004
19.10	0.26	1.60	0.08	0.752	0.010	0.063	0.003	67.60	0.60	2.40	0.09	2.661	0.024	0.094	0.004
20.10	0.27	1.60	0.08	0.791	0.011	0.063	0.003	69.60	0.62	2.40	0.09	2.740	0.024	0.094	0.004
21.10	0.27	1.60	0.08	0.831	0.011	0.063	0.003	19.50	0.26	3.00	0.09	0.768	0.010	0.118	0.004
22.10	0.28	1.60	0.08	0.870	0.011	0.063	0.003	21.50	0.28	3.00	0.09	0.846	0.011	0.118	0.004
25.10	0.30	1.60	0.08	0.988	0.012	0.063	0.003	22.50	0.28	3.00	0.09	0.886	0.011	0.118	0.004
27.10	0.32	1.60	0.08	1.067	0.013	0.063	0.003	24.50	0.30	3.00	0.09	0.965	0.012	0.118	0.004
29.10	0.33	1.60	0.08	1.146	0.013	0.063	0.003	25.50	0.31	3.00	0.09	1.004	0.012	0.118	0.004
32.10	0.35	1.60	0.08	1.264	0.014	0.063	0.003	26.50	0.31	3.00	0.09	1.043	0.012	0.118	0.004
35.10	0.37	1.60	0.08	1.382	0.015	0.063	0.003	27.50	0.32	3.00	0.09	1.083	0.013	0.118	0.004
37.10	0.39	1.60	0.08	1.461	0.015	0.063	0.003	29.50	0.33	3.00	0.09	1.161	0.013	0.118	0.004
3.60	0.14	2.40	0.09	0.142	0.006	0.094	0.004	31.50	0.35	3.00	0.09	1.240	0.014	0.118	0.004
4.60	0.15	2.40	0.09	0.181	0.006	0.094	0.004	32.50	0.36	3.00	0.09	1.280	0.014	0.118	0.004
5.60	0.16	2.40	0.09	0.220	0.006	0.094	0.004	34.50	0.37	3.00	0.09	1.358	0.015	0.118	0.004
6.60	0.16	2.40	0.09	0.260	0.006	0.094	0.004	35.50	0.38	3.00	0.09	1.398	0.015	0.118	0.004
7.60	0.17	2.40	0.09	0.299	0.007	0.094	0.004	36.50	0.38	3.00	0.09	1.437	0.015	0.118	0.004
8.60	0.18	2.40	0.09	0.339	0.007	0.094	0.004	37.50	0.39	3.00	0.09	1.476	0.015	0.118	0.004
9.60	0.19	2.40	0.09	0.378	0.007	0.094	0.004	39.50	0.41	3.00	0.09	1.555	0.016	0.118	0.004
10.60	0.19	2.40	0.09	0.417	0.007	0.094	0.004	41.50	0.42	3.00	0.09	1.634	0.017	0.118	0.004
11.60	0.20	2.40	0.09	0.457	0.008	0.094	0.004	42.50	0.43	3.00	0.09	1.673	0.017	0.118	0.004
12.60	0.21	2.40	0.09	0.496	0.008	0.094	0.004	44.50	0.44	3.00	0.09	1.752	0.017	0.118	0.004
13.60	0.22	2.40	0.09	0.535	0.009	0.094	0.004	49.50	0.48	3.00	0.09	1.949	0.019	0.118	0.004
14.60	0.22	2.40	0.09	0.575	0.009	0.094	0.004	54.50	0.51	3.00	0.09	2.146	0.020	0.118	0.004
15.60	0.23	2.40	0.09	0.614	0.009	0.094	0.004	55.50	0.52	3.00	0.09	2.185	0.020	0.118	0.004
16.60	0.24	2.40	0.09	0.654	0.009	0.094	0.004	57.50	0.53	3.00	0.09	2.264	0.021	0.118	0.004
17.60	0.25	2.40	0.09	0.693	0.010	0.094	0.004	59.50	0.55	3.00	0.09	2.343	0.022	0.118	0.004
18.60	0.25	2.40	0.09	0.732	0.010	0.094	0.004	62.50	0.57	3.00	0.09	2.461	0.022	0.118	0.004
19.60	0.26	2.40	0.09	0.772	0.010	0.094	0.004	64.50	0.58	3.00	0.09	2.539	0.023	0.118	0.004
20.60	0.27	2.40	0.09	0.811	0.011	0.094	0.004	69.50	0.62	3.00	0.09	2.736	0.024	0.118	0.004
21.60	0.28	2.40	0.09	0.850	0.011	0.094	0.004	74.50	0.65	3.00	0.09	2.933	0.026	0.118	0.004
24.60	0.30	2.40	0.09	0.969	0.012	0.094	0.004	79.50	0.68	3.00	0.09	3.130	0.027	0.118	0.004
27.60	0.32	2.40	0.09	1.087	0.013	0.094	0.004	84.50	0.72	3.00	0.09	3.327	0.028	0.118	0.004
29.60	0.33	2.40	0.09	1.165	0.013	0.094	0.004	89.50	0.75	3.00	0.09	3.524	0.030	0.118	0.004
31.60	0.35	2.40	0.09	1.244	0.014	0.094	0.004	94.50	0.79	3.00	0.09	3.720	0.031	0.118	0.004
34.60	0.37	2.40	0.09	1.362	0.015	0.094	0.004	99.50	0.82	3.00	0.09	3.917	0.032	0.118	0.004
35.60	0.38	2.40	0.09	1.402	0.015	0.094	0.004	104.50	0.86	3.00	0.09	4.114	0.034	0.118	0.004

O-Ring Standard Size (BS 4518)